(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 7 July 2005 (07.07.2005)

PCT

(10) International Publication Number WO 2005/062412 A2

(51) International Patent Classification⁷: H01M 8/10, 8/04, 4/86, 4/88, 4/92

(21) International Application Number:

PCT/JP2004/019292

(22) International Filing Date:

16 December 2004 (16.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-427035 24 December 2003

24 December 2003 (24.12.2003) JP

(71) Applicant (for all designated States except US): TOY-OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toy-ota-cho, Toyota-shi, Aichi 4718571 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): AOYAMA, Satoshi [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyotacho, Toyota-shi, Aichi 4718571 (JP). ITO, Naoki [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). II,JIMA, Masahiko [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). OGINO, Shigeru [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). KIMURA, Kenji [JP/JP]; c/o

Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). SATO, Hiromichi [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). IZAWA, Yasuhiro [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). IGUCHI, Satoshi [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

- (74) Agent: TOKKYO GYOMUHOJIN MEISEI INTER-NATIONAL PATENT FIRM; Mitsui-Sumitomo Bank Bldg., 7th floor, 18-19, Nishiki 2-chome, Naka-ku, Nagoya-shi, Aichi 4600003 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: FUEL CELL



(57) Abstract: A fuel cell of the invention has a hydrogen permeable metal layer, which is formed on a plane of an electrolyte layer that has proton conductivity and includes a hydrogen permeable metal. The fuel cell includes a higher temperature zone and a lower temperature zone that has a lower temperature than the higher temperature zone. The hydrogen permeable metal layer includes a lower temperature area A corresponding to the lower temperature zone and a higher temperature area B corresponding to the higher The lower temperature temperature zone. area A and the higher temperature area B have different settings of composition and/or layout of components. This arrangement effectively prevents potential deterioration of cell performance due to an uneven distribution of internal temperature of the fuel cell including the hydrogen permeable metal layer.

WO 2005/062412 A2



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

 without international search report and to be republished upon receipt of that report